




PRESS. SEAL. RELEASE.

BASIN POP-UP WASTE

AT A GLANCE




BEST FOR
Bathroom basins



MATERIAL
Crafted from Stainless
Steel 304



INSTALLATION
For overflow and
non overflow
pop-up wastes



Specifications



MATERIAL

Stainless **304** Steel



CARTRIDGE

Fist basin hole · **40-48 mm**



CONNECTIONS

Standard **G1-1/4"**




MOUNTING

Outlet thread · **$\varnothing 32$ mm**



DIMENSIONS

Overall height **80 mm** · diameter **$\varnothing 66$ mm**



What's in the box

INCLUDED

1x Pop-Up Waste

1x Fixing Nut

2x Fixing Screws

1x Installation Instructions

EXPLODED VIEW

① Pop-Up Stopper Cap

② Stopper Sealing Ring

③ Waste Body and Flange

④ Friction Washer

⑤ Fixing Nut

Finish Options



Antique Brass
AEA



Brushed Nickel
AEA



Brushed Brass
PVD



Brushed Copper
PVD




Gun Metal
PVD

Installation Guide

PLUMBER REQUIRED AS/NZS 3500


01



Prepare the waste

Remove the fixing nut, friction washer and rubber sealing washer from the waste body.


02



Install the waste body

Ensure the overflow openings in the waste body align with the basin's overflow channel.


03



Secure and connect

From below the basin, fit the rubber sealing washer, friction washer and fixing nut.

04



Test the installation

Check the waste connection and overflow system for correct drainage and leaks.



FINAL CHECK - TURN ON & TEST

Turn on the water supply and test for correct operation and leaks. Do not seal or tile until the tap is fully tested.

Care & Maintenance



MILD SOAP & WARM WATER

Clean with mild soap and warm water.



SOFT CLOTH ONLY

Use soft cloth only.



NO CITRUS, BLEACH OR ABRASIVE CLEANERS

These can damage the surface and affect longevity

Compliance



WATERMARK CERTIFIED

AS/NZS 3718



WELS APPROVED



NCC LEAD-FREE

LESS THAN 0.25%



INSTALLATION STANDARD

AS/NZS 3500.1 & 3500.4