



SIMPLE GESTURES. EVERYDAY EASE

HAND WAND WITH ADJUSTABLE RAIL

AT A GLANCE



BEST FOR

Ideal for everyday use — whether you're rinsing down, resetting, or washing the kids after a long day




FEEL

Smooth height-adjustable slider, this rail adapts to every user and every routine



INSTALLATION

Wall-mounted, plumber required



Specifications



MATERIAL

Solid Lead Free **DZR** Brass
Wand Hose Material:
Stainless Steel 304 (**SS304**)



FLOW RATE

8.5 L/min · WELS 3 Star



PRESSURE RANGE

50–800 kPa




MOUNTING

Wall-mounted



DIMENSIONS

Shower wand diameter **$\varnothing 25$ mm** · Shower wand length
200 mm · Overall length **700 mm** · Wall projection **50 mm**



 What's in the box

INCLUDED

1x	Shower Wand
1x	Adjustable Hand Shower Bracket
2x	Wall Mounts
2x	Fixing Screws
2x	Hollow Wall Anchors
2x	Cover Rings
1x	150cm Metal Hose
1x	Spare Rubber Washer
1x	Spare Grub Screw

EXPLODED VIEW

- ① Wall Mounting
- ② Grub Screw
- ③ Mini Hex Wrench
- ④ Adjustable Rail
- ⑤ Water Connection
- ⑥ Hand Wand Hose
- ⑦ Shower Wand

Finish Options



Antique Brass
AEA




Brushed Nickel
AEA



Brushed Brass
PVD



Brushed Copper
PVD




Gun Metal
PVD

Installation Guide

PLUMBER REQUIRED AS/NZS 3500


01



Mark Wall Fixings

Mark the positions for the wall fixings on the wall. Refer to the image above for the measurements. Screw the water outlet cover into place.


02



Install Wall Mountings

Fix the wall mountings to the wall using the fixing screws.


03



Attach Main Body

Place the main body onto the wall fixings. Tighten the grub screw with the Allen key to secure it in place.

04



Connect Hose

Connect one end of the hose to the water outlet and the other end to the round wand.



FINAL CHECK • TURN ON & TEST

Do not seal or tile until the tested and confirmed leak-free.

Care & Maintenance



MILD SOAP & WARM WATER

Clean with mild soap and warm water.



SOFT CLOTH ONLY

Use soft cloth only.



NO CITRUS, BLEACH OR ABRASIVE CLEANERS

These can damage the surface and affect longevity

Compliance



WATERMARK CERTIFIED

AS/NZS 3718



WELS APPROVED

3 STAR • 8.5 L/MIN



NCC LEAD-FREE

LESS THAN 0.25%



INSTALLATION STANDARD

AS/NZS 3500.1 & 3500.4