


The installation instruction apply for below products :



Important Information

It is recommended that this product is installed by a qualified professional.

Please remove all packaging and check this product to ensure it has not been damaged or any parts are missing.

Before installing please make sure this is the correct model and you have all the parts required for installation and usage.

The printed picture is for reference only, this product is according to the actual goods.

Please check all the accessories are present.

Always read these instructions carefully and keep for future reference

Operating Information

Operating Pressure

Minimum operating pressure 0.5 bar

Maximum operating pressure 8 bar

Pre-Installation

1. Before installing the Shower set, flush through the pipe work to remove any debris & other impurities that can enter the Shower set.
2. Turn off water supply at the isolation valves before commencing with work.

Warranty Requirements

For full warranty terms and conditions please visit the warranty section of our website.

Please pay attention to the below. Failure to do so will void your warranty:

1. Do not use acid cleansers
2. Do not use abrasive cleansers
3. Do not use abrasive cloths

Maintenance & Care

To avoid damage it is necessary to consider the below guidelines.

1. To clean the Shower set surface use clean hot soapy water. ONLY use soft fabric cloths.
2. DO NOT use cleaning solutions that contain hydrochloric acid, formic acid, concentrated caustic soda, chlorine or acetic acid as they can cause considerable damage.
3. DO NOT use any coarse cleaning powders or brushed to clean the Shower set.
4. If there is irregular water pressure & water flow is reduced, please check if the spout is clean, if not brush the spout after vinegar soaking.

PLEASE MAKE SURE YOU FULLY TEST YOUR PRODUCT BEFORE TILING ETC.
WE WILL NOT BE RESPONSIBLE FOR ANY COSTS INVOLVED IN REMOVAL OF
THE TAP IF YOU FIND THERE IS A FAULT.

Installation

Prepare all accessories according to picture (1), there is hot water on the left
The water inlet and cold water inlet are on the right side. (Note that the left and right sides are
View the product from the front).

1. Build the faucet body and place it in the desired position above the hot and cold water supply.
Mark the opening dimensions as shown below:
2. Unscrew the main body and install the hot (red) and cold (blue) hoses into the main body.
3. Rebuild the body and connect the hoses to the heat and cold sources. Check
If there is leakage, tighten and secure.
4. Connect the hand shower to the freestanding faucet body.
5. After completing the above steps, please check whether the product is leaking.

Installation steps

